

Page1 of 1Certificate No:LR212Issue Date:05/07Expiry Date:04/07

LR21209217TA 05/07/2021 04/07/2026

Appendix

Rating:

Application parameters	Steel washers	Stainless steel washers	254 SMO washers	Alloy C-276 washers	Alloy 718 washers
Steel type	EN 1.7182 or equivalent	EN 1.4404 or equivalent	EN 1.4547 or equivalent	EN 2.4819 or equivalent	EN 2.4667 or equivalent
Bolt sizes	M3-M130	M3-M80	M3-M39	M3-M39	M3-M39
Washer type	NL3-NL130	NL3ss-NL8oss	NL3ss-NL39ss	NL3ss-NL39ss	NL3ss-NL39ss
Washer hardness	≥465 HV1	≥ 520 HV0.05	≥600 HV0.05	≥ 520 HV0.05	≥620 HV0.05
Temperature range	- 50°C to 200 °C	- 160°C to 500 °C	-160°C to 500 °C	-160°C to 500 °C	-160°C to 700 °C

Lloyd's Register Group Limited, its affiliates and subsidiaries and their respective officers, employees or agents are, individually and collectively, referred to in this clause as 'Lloyd's Register'. Lloyd's Register assumes no responsibility and shall not be liable to any person for any loss, damage or expense caused by reliance on the information or advice in this document or howsoever provided, unless that person has signed a contract with the relevant Lloyd's Register entity for the provision of this information or advice and in that case any responsibility or liability is exclusively on the terms and conditions set out in that contract.